



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove)    [Search Tips](#)

**Text Search: 'HSTT150-CC'**

Your search criteria matched only one product, shown below

## HSTT150-CC



Flexible Ployolefin DRY-SHRINK<sup>TM</sup>Heat Shrink Tubing

- General Purpose heat shrink tubing for dry locations
- Applications include insulating, protecting, harnessing and identifying wires.
- Material Type: Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 275°F (-55°C to 135°C)
- Flammability Rating: Flame retardant EXCEPT clear
- Voltage: 600 V
- UL Recognized, CSA Certified
- Mil Spec: AMSDTL-23053/5 Class 1 (Colors) Class 2 (Clear)

|                                        |                                           |
|----------------------------------------|-------------------------------------------|
| Part Number                            | HSTT150CC                                 |
| RoHS Compliancy Status                 | Compliant                                 |
| Part Description                       | Thin Wall Polyolefin Heat Shrink          |
| Material                               | Polyolefin cross-linked                   |
| Color                                  | Clear                                     |
| Military Specification                 | AMS-DTL-23053/5 Class 2                   |
| CE Compliant                           | No                                        |
| CE Marking                             | No                                        |
| Length Per Reel (ft.)                  | 100                                       |
| Length Per Reel (m)                    | 30.5                                      |
| Max. Recovered I.D. (In.)              | .750                                      |
| Max. Recovered I.D. (mm)               | 19.0                                      |
| Min. Expanded I.D. (In.)               | 1.50                                      |
| Min. Expanded I.D. (mm)                | 38.1                                      |
| Nominal Diameter / Size                | 1.50                                      |
| Nominal Recovered Wall Thickness (In.) | .040                                      |
| Nominal Recovered Wall Thickness (mm)  | 1.0                                       |
| Pricing Description                    | Heat Shrink Thin, 1.5"(38.1mm) Dia, Clear |
| Shrink Ratio                           | 2:1                                       |
| Temperature Range                      | -67°F to 275°F (-55°C to 135°C)           |
| Min. Order UOM                         | RL                                        |
| Min. Order Qty.                        | 1                                         |
| BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>            |
| Add to Favorite Product List           |                                           |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.