



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'HSTT38-48-Q45'

Your search criteria matched only one product, shown below

HSTT38-48-Q45



- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
 - Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- For clear, add "C" to end of part number package suffix (Example HSTT05 -48-QC). Contact customer service for additional color information.

Meets Mil Spec AMSDTL-23053/5 Class 1(Colors), Class 2 (Clear)

	Part Number	HSTT3848-Q45
	RoHS Compliance Status	Compliant
	Part Description	Thin Wall Polyolefin Heat Shrink
	Material	Flame retardant polyolefin cross-linked except clear
	Color	Yellow/Green
	CSA Certified	Yes
	Military Specification	AMS-DTL-23053/5 Class 1
	UL Recognized	E122770
	Length (ft.)	4
	Length (m)	1.2
	CE Compliant	No
	CE Marking	No
	Flammability Rating	Flame Retardant
	Max. Recovered I.D. (In.)	.187
	Max. Recovered I.D. (mm)	4.8
	Min. Expanded I.D. (In.)	.375
	Min. Expanded I.D. (mm)	9.5
	Nominal Diameter / Size	.375
	Nominal Recovered Wall Thickness (In.)	.025
	Nominal Recovered Wall Thickness (mm)	.6
	Pricing Description	Heat Shrink Thin, .38"(9.5mm) Dia, Yellow/Green
	Shrink Ratio	2:1
	Temperature Range	-67°F to 275°F (-55°C to 135°C)
	Min. Order UOM	PC
	Min. Order Qty.	25
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.