

[support](#) | [locate distributor](#) | [about panduit](#) | [contact us](#)*World Leader in Network and Electrical Solutions*[HOME](#) | [SOLUTIONS](#) | [RESOURCES](#) | [PRODUCTS](#) | [SERVICES](#) | [LEARNING](#)SEARCH Current refinements (click ☐ to remove)☒ **Region** ▶ **USA** ☒ **Product Family** ▶ **HSTTA Heat Shrink** ☒ **Text Search:** 'HSTTA25-48-TL'**Your search criteria matched only one product, shown below.****Dual Wall Polyolefin DAMP-SHRINK™ Heat Shrink Tubing in 4 ft Pieces**

- For damp locations
- Flexible tubing with an adhesive inner wall which seals and protects components from moisture and corrosion
- The 3:1 shrink ratio is a benefit when working with connector-to-cable transitions
- Material Type: Polyolefin Cross-Linked with adhesive
- Shrink Ratio: 3:1
- Temperature Range: -67°F to 230°F (-55°C to 110°C)
- Flammability: Outer wall flame retardant
- Voltage Rating: 600V
- Mil Spec: AMS-DTL-23053/4 Class 3

Part Number:	HSTTA25-48-TL
RoHS Compliancy Status:	Compliant
Part Description:	Dual Wall Adhesive Lined Thin Wall Heat Shrink
Material:	Polyolefin cross-linked with adhesive.
Color:	Black
Military Specification:	AMS-DTL-23053/4 Class 3
Length (ft.):	4
Flammability Rating:	Outer Wall Flame Retardant
Max. Recovered I.D. (In.):	.080
Max. Recovered I.D. (mm):	2.0
Min. Expanded I.D. (In.):	.250
Min. Expanded I.D. (mm):	6.4
Nominal Diameter / Size:	1/4
Nominal Recovered Wall Thickness (In.):	.040
Nominal Recovered Wall Thickness (mm):	1.0
Shrink Ratio:	3:1
Temperature Range:	-67°F to 230°F
Min. Order UOM:	PC
Min. Order Qty.:	250
BOM Qty. (# of Pkgs.)	0
Add to My Catalog	☐

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2007, PANDUIT CORP. All rights reserved.