



Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFHSTTA Heat S
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'HSTTA50-48-T'

Your search criteria matched only one product, shown below

HSTTA50-48-T



Dual Wall Polyolefin DAMP-SHRINK™ Heat Shrink Tubing in 4 ft Pieces

- For damp locations
- Flexible tubing with an adhesive inner wall which seals and protects components from moisture and corrosion
- The 3:1 shrink ratio is a benefit when working with connector -to-cable transitions
- Material Type: Polyolefin Cross -Linked with adhesive
- Shrink Ratio: 3:1
- Temperature Range: -67°F to 230°F (-55°C to 110°C)
- Flammability: Outer wall flame retardant
- Voltage Rating: 600 V
- Mil Spec: AMSDTL-23053/4 Class 3

Part Number	HSTTA50-48-T
RoHS Compliancy Status	Compliant
Part Description	Dual Wall Adhesive Lined Thin Wall Heat Shrink
Material	Polyolefin cross-linked with adhesive.
Color	Black
Military Specification	AMS-DTL-23053/4 Class 3
Length (ft.)	4
Length (m)	1.2
CE Compliant	No
CE Marking	No
Flammability Rating	Outer Wall Flame Retardant
Max. Recovered I.D. (In.)	.160
Max. Recovered I.D. (mm)	4.1
Min. Expanded I.D. (In.)	.500
Min. Expanded I.D. (mm)	12.7
Nominal Diameter (In.)	.500
Nominal Diameter (mm)	12.7
Nominal Recovered Wall Thickness (In.)	.070
Nominal Recovered Wall Thickness (mm)	1.8
Pricing Description	Heat Shrink Thin, Adhesive, .50"(12.7mm) Dia, Black
Shrink Ratio	3:1
Temperature Range	-67°F to 230°F(-55°C to 110°C)
Min. Order UOM	PC
Min. Order Qty.	200
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.