



Search Results

Evaluate

- FAQ's

Design a Solution

- Part Drawings

- PDFPVC Heat Shr

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'HSTTP05-CY'

Your search criteria matched only one product, shown below

HSTTP05-CY



PVC DRY-SHRINK™ Heat Shrink Tubing in Reels

- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance
- Material Type: Polyvinyl Chloride Cross-Linked
- Shrink Ratio: 2:1
- Temperature Range: -4°F to 221°F (-20°C to 105°C)
- Voltage: 600V
- UL VW-1 Recognized, CSA Certified
- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance

Part Number	HSTTP05CY
RoHS Compliance Status	Compliant
Note	HSTTP05CY replaces HSTTP05C
Part Description	Flexible, Flame Retardant PVC material offers good cut through and solder resistance.
Material	Polyvinyl Chloride CrossLinked
Color	Black
CSA Certified	Yes
UL Recognized	E122770
CE Compliant	No
CE Marking	No
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	100
Length Per Reel (m)	30.5
Max. Recovered I.D. (In.)	.023
Max. Recovered I.D. (mm)	0.6
Min. Expanded I.D. (In.)	.046
Min. Expanded I.D. (mm)	1.2
Nominal Diameter (In.)	.046
Nominal Diameter (mm)	1.2
Nominal Recovered Wall Thickness (In.)	.020
Nominal Recovered Wall Thickness (mm)	0.5
Pricing Description	Heat Shrink Thin PVC, .05"(1.2mm) Dia Black
Shrink Ratio	2:1
Temperature Range	-4°F to 221°F (-20°C to 105°C)
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.