



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor
- Install & Maintain
- Installation Instructions
 - PDFPan-Shrink H ..

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'HSTTV05-Y'

Your search criteria matched only one product, shown below

HSTTV05-Y



- Small package fits easily in tool box
- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- Available in various colors for permanent, cost effective color coding

Meets Mil Spec AMS-DTL-23053/5 Class 3.

	Part Number	HSTTV05-Y
	RoHS Compliancy Status	Compliant
	Part Description	Thin Wall Polyolefin Heat Shrink (UL224 VW1)
	Product Type	Heat Shrink
	Material	Highly flame retardant polyolefin cross-linked^^
	Color	Black
	CSA Certified	Yes
	Military Specification	AMS-DTL-23053/5 Class 3
	UL Recognized	E122770
	Length (In.)	6.00
	Length (mm)	152.4
	Flammability Rating	UL224 VW-1
	Max. Recovered I.D. (In.)	.023
	Max. Recovered I.D. (mm)	0.6
	Min. Expanded I.D. (In.)	.046
	Min. Expanded I.D. (mm)	1.2
	Nominal Diameter (In.)	.046
	Nominal Diameter (mm)	1.2
	Nominal Recovered Wall Thickness (In.)	.016
	Nominal Recovered Wall Thickness (mm)	0.4
	Pieces per Package	26
	Pricing Description	Heat Shrink Thin VW1,.05"(1.2mm) Dia, Black
	Shrink Ratio	2:1
	Temperature Range	-67°F to 257°F (-55°C to 125°C)
	Min. Order UOM	PK
	Min. Order Qty.	1
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.