



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#)

Text Search: 'HSTTV75-T2'

Your search criteria matched only one product, shown below

HSTTV75-T2



Flexible Polyolefin VW-1 DRY-SHRINKTM Heat Shrink Tubing in Bulk Reels

- For dry locations
- Highly flame retardant Meets UL VW-1 Rating
- Fast Shrink Time
- Material Type: Highly Flexible Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range: -67°F to 257°F (-55°C to 125°C)
- Voltage: 600V
- UL VW-1 Recognized, CSA Certified
- Mil Spec: AMSDTL-23053/5 Class 3

	Part Number	HSTTV75-T2
	RoHS Compliancy Status	Compliant
	Part Description	Thin Wall Polyolefin Heat Shrink (UL224 VW1)
	Material	Polyolefin cross-linked
	Color	Red
	CSA Certified	Yes
	Military Specification	AMS-DTL-23053/5 Class 3
	UL Recognized	E122770
	Length (ft.)	200
	Length (m)	61.1
	CE Compliant	No
	CE Marking	No
	Flammability Rating	UL224 VW-1
	Length Per Reel (ft.)	200
	Length Per Reel (m)	61.1
	Max. Recovered I.D. (In.)	.375
	Max. Recovered I.D. (mm)	9.5
	Min. Expanded I.D. (In.)	.750
	Min. Expanded I.D. (mm)	19.0
	Nominal Diameter (In.)	.750
	Nominal Diameter (mm)	19.0
	Nominal Recovered Wall Thickness (In.)	.03
	Nominal Recovered Wall Thickness (mm)	0.8
	Pricing Description	Heat Shrink Thin VW1, .75"(19.0mm) Dia, Red
	Shrink Ratio	2:1
	Temperature Range	-67°F to 257°F (55°C to 125°C)
	Min. Order UOM	RL
	Min. Order Qty.	1
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.