

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFNon-Shrink P..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Current refinements (click to remove) Search Tips

Text Search: 'TV105-1.0L '

Your search criteria matched only one product, shown below

**PLEASE
SEE THE
DESCRIPTION**

Non-Shrink oil resistant flexible clear tubing on reel

- Provides insulation and protection for lead wires wire harness assemblies soldered joints and components in electrical and electronic equipment
- Material: Polyvinyl chloride (PVC)
- Voltage Rating: 300V and 600V
- All purpose flexible non -shrinkable
- Resistant to heat and moisture

Applicable Specifications:

- UL224 VW-1
- UL Recognized
- CSA C22.2 No. 198.1 (OFT)
- ASTM D-922 Grade CFR
- MIL-I-631 Type F, Form U, Grade C- Class 1 Category 1

Part Number	TV105-1.0CY
RoHS Compliancy Status	Compliant
Note	TV105-1.0CY replaces TV105-1.0L
Part Description	PVC Non-Shrink Tubing, 105°C rated
Product Type	Non-Shrink Polyvinyl Chloride Tubing
Material	Polyvinyl Chloride
Color	Clear
CSA Certified	Yes
CSA Specification	CSA C22.2 No. 198.1 (OFT)
UL Recognized	E122770
UL Recognized Specification	UL224 VW-1
CE Compliant	No
Flammability Rating	VW-1
Length Per Reel (ft.)	100
Length Per Reel (m)	30.5
Max. Inside Diameter (In.)	1.036
Max. Inside Diameter (mm)	26.31
Max. Voltage Rating	600 V
Min. Inside Diameter (mm)	25.40
Minimum Inside Diameter (In.)	1.00
Nominal Size	1
Pricing Description	Vinyl Tubing, 1" (25.4mm), 600V, Clear
Temperature Range	-4°F – 221°F (-20°C – 105°C)
Type	Non-Shrink Polyvinyl Chloride Tubing
Wall Thickness (In.)	0.035
Wall Thickness (mm)	0.89
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.