

Products

- Products Overview
- Product Search
- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
- PDF Copper Lug, ..
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click to remove) Search Tips

Part Description > Blank tongue, standard barrel lug, 1000 kcmil cable.

Your search criteria matched only one product, shown below

LCD1000-00-3



- For Use with Stranded Copper Conductors
- Color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection
 - Inspection window to visually assure full conductor insertion
 - Tin-plated to inhibit corrosion
 - UL Recognized and CSA Certified to 35 KV** and temperature rated to 90°C when crimped with Panduit and specified competitor crimping tools and dies
- LCD Blank Tongue-** Reduce your inventory levels and customize your hole and spacing requirements with blank tongue lugs.

Part Number	LCD1000-00-3
RoHS Compliancy Status	Compliant
Part Description	Blank tongue, standard barrel lug, 1000 kcmil cable.
Product Type	Compression Connectors- Lugs
Material	Tin-Plated Copper
CSA Certified	Yes
UL Recognized	Yes
Length (In.)	5.77
Length (mm)	146.6
Copper Conductor Size	1000 kcmil
Tongue Width (In.)	2.17
Barrel Length (In.)	1.88
Angle	Straight
CE Compliant	No
Panduit Color Code	White
Panduit Die Index No.	P125
Pricing Description	Copper Compression Lug, Long Blank Tongue, 1000 Kcmil
Tongue Thickness	0.32
Tongue Type	Standard
Tongue Width (mm)	55.1
Wire Strip Length (In.)	1 15/16
Wire Strip Length (mm)	49.2
Min. Order UOM	PC
Min. Order Qty.	1
Burndy Die Index No.	27
T&B Die Index No.	125
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.