



Keyword, Part Number or Cross-Ref



EDNF18-250FIB-L

Disconnect

StrongHold™ Female Disconnect, nylon fully insulated, 22 - 18 AWG, .250 X .032 tab size.

Specifications

Disconnect Type	Female Disconnect
Barrel Type	Butted Seam
Maximum Wire Size (AWG)	22 - 18 AWG (0.5 - 1.0)
Wire Strip Length (In.)	0.28125
Wire Strip Length (mm)	7.1
Insulation Type	Nylon - Fully Insulated
Color	Red
Overall Length (In.)	0.84
Overall Length (mm)	21.3

Maximum Wire Insulation Diameter (In.)	0.136
Maximum Wire Insulation Diameter (mm)	3.45
Tab Size (In.)	0.250 x 0.032
Tab Size (mm)	6.3 x 0.8
Maximum Voltage (V)	600
Maximum Operating Temperature (°C)	125
Maximum Operating Temperature (°F)	257

Finish/Coating	Tin-Plated
Overall Width (In.)	0.35
Overall Width (mm)	8.9

Standards Met	UL, CSA
For Use With	CT-100A, CT-600-A, CT-1525, CT-2300/ST, CT-2500/L
RoHS Compliance Status	Compliant
Min. Order Qty.	50

Packaging Details

UPC	07498327996
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0103

Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	0.1031

Resources

Part Drawings	Fully Nylon Insulated Female Disco 250 & 188, 22-14	US English	PDF348.22KB		
---------------	---	------------	------------------------	---	---

Related Products



DNF18-250FIB-3K

The vibration resistant female disconnect is made of brass and is tin-plated. It is fully insulated in a red, nylon standard receptacle housing. It has a tab size of 0.250 x 0.032" (6.3 x 0.8 mm) and supports a wire range of 22-18 AWG (0.5-1.0 mm²). It is 0.84" (21.3 mm) long and 0.35" (8.9 mm) wide. The disconnect has a



DNF14-250FIB-3K

The vibration resistant female disconnect is made of brass and is tin-plated. It is fully insulated in a blue, nylon housing. It has a tab size of 0.250 x 0.032" (6.3 x 0.8 mm) and supports a wire range of 16-14 AWG (1.5-2.5 mm²). It is 0.84" (21.3 mm) long and 0.35" (8.9 mm) wide. The disconnect has a funnel entry



DNF10-250FIB-2K

The vibration resistant female disconnect is made of brass and is tin-plated. It is fully insulated in yellow, nylon standard receptacle housings. It has a tab size of 0.250 x 0.032" (6.3 x 0.8 mm) and supports a wire range of 12-10 AWG (4.0-6.0 mm²). It is 0.96" (24.4 mm) long and 0.35" (8.9 mm) wide. The disconnect has a

funnel entry barrel configuration and a butted seam barrel. It comes in reels of 3000 pieces.

barrel configuration and a butted seam barrel. It comes in reels of 3000 pieces.

funnel entry barrel configuration and a butted seam barrel. It comes in reels of 2000.



Email Support

Email support available
24/7



800-777-3300

Monday through Thursday
7:00 am-6:30 pm CST
Friday 7:00 am-6:00 pm
CST



Where to Buy

Find a Panduit Distributor
or Partner

ABOUT US

Research and Development

Media Resources

World Headquarters

Awards

Partner Ecosystem

CAREERS AT PANDUIT

THE HUB – PARTNER PORTAL

PRODUCT REGISTRATION

PANDUIT CONNECTIONS BLOG



GET OUR CATALOG

Download the PDF or request a copy be
mailed to you.

Which catalog would you like?



► DOWNLOAD ► REQUEST COPY

