



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Draw ings
 - PDF-Female Disco ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'D18-250B-M'

Your search criteria matched only one product, shown below

D18-250B-M



- Non-insulated barrel can be used to provide an economical termination when insulation is not required

	Part Number	D18-250B-M
	RoHS Compliancy Status	Compliant
	Part Description	Female Disconnect, 22 – 18 AWG, .250 x .032 tab size, non-insulated, butted seam.
	Product Type	Disconnects
	CSA Certified	Yes
	UL Listed	No
	Height (In.)	.12
	Length (In.)	.63
	Width (In.)	.30
	Angle	straight
	Pricing Description	Female Disconnect, non-insulated, 22 - 18 AWG, .250 x .032 tab size, butted seam
	Tab Size (In.)	.250 x .032
	Tool	CT-100A
	Wire Range	22 – 18 AWG
	Wire Range (mm²)	0.5 – 1.0
	Min. Order UOM	PC
	Min. Order Qty.	1000
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.