



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
 - PDFMetric Femal ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'DMNF2488FIB-3K'

Your search criteria matched only one product, shown below

DMNF2-488FIB-3K



Standard nylon provides an insulation support for normal requirements. The fully Insulated design gives excellent flashover protection and the funnel entry speeds wire insertion for increased productivity.

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Disconnects available in common industry tab sizes
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection

	Part Number	DMNF2488FIB-3K
	RoHS Compliancy Status	Compliant
	Part Description	Metric reel-fed female disconnect, 1.5 - 2.5mm ² wire range, 4.8mm x .8mm tab size, nylon fully insulated, funnel entry.
	Product Type	Disconnects – Metric ReelFed
	CSA Certified	Yes
	UL Listed	Yes
	Height (mm)	4.6
	Length (mm)	19.8
	Width (mm)	7.4
	CA-800 Series Crimp Die	CD-800-5
	CA9 Series Crimp Die	CD9-5A
	Max. Ins.	4.0
	Panduit Color Code	Blue
	Pieces Per Reel	3000
	Pricing Description	Metric Female Disconnect, nylon fully insulated, 1.5- 2.5mm ² wire range, 4.8 x .8mm tab size, funnel entry
	Tab Size (mm)	4.8 x .8
	Wire Range (mm ²)	1.5 – 2.5
	Min. Order UOM	PC
	Min. Order Qty.	3000
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.