



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'DPF14-250FIMB-K'

Your search criteria matched only one product, shown below

DPF14-250FIMB-K



*DiscoGrip*M,3[Trade]»Fully Insulated Male Disconnects. Premium grade nylon housing provides insulation crimp for superior wire insulation strain relief. Nylon insulation is rated at 600 volts and designed for up to 105° C (221° F) operating temperature.

- Continuously molded design provides reliable, consistent performance through the applicator for a high quality termination every time
- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Premium nylon insulation retains its shape when crimped and provides a tight grip around the wire insulation for maximum strain relief
- Oversized housing designed for maximum versatility to mate with most commercially available fully insulated female disconnects
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection

- UL and CSA rated up to 600 V per UL 310

Part Number	DPF14-250FIMB-K
RoHS Compliancy Status	Compliant
Part Description	Male disconnect (oversized housing), nylon fully insulated, funnel entry, insulation support, internal wire stop, 16 – 14 AWG wire range, .250 x .032 in. (6.3 x .8mm) tab size.
Product Type	Disconnects - Reel Fed
CSA Certified	Yes
UL Listed	Yes
Height (In.)	.34
Length (In.)	.92
Width (In.)	.46
CA-800 Series Crimp Die	CD-800-11
CA9 Series Crimp Die	CD9-11B
Max. Ins.	.156
Panduit Color Code	Blue
Pieces Per Reel	1000
Pricing Description	Male Disc,Premium Nylon FI,16-14AWG,250X032
Tab Size (In.)	.250 x .032
Tab Size (mm)	6.3 x .8
Wire Range	16 – 14 AWG
Wire Range (mm²)	1.5 - 2.5
Min. Order UOM	PC
Min. Order Qty.	1000
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.