



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor
- Install & Maintain
- Installation Instructions
- PDFThick Wall H ..

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'HST1.5-9-X'

Your search criteria matched only one product, shown below

HST1.5-9-X



- Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
 - Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
 - Thick wall product seals and insulates in one step to speed installation
- * For red, add 2 to end of part number package suffix (Example HST0.4 -3-Q2).
- ## Meets Mil Spec AMS -DTL-23053/15 Class 1.

Part Number	HST1.5-9-X
RoHS Compliancy Status	If RoHS Decabrome Free Part required use HST1.5-XY
Note	Call Customer Service for Pricing, Availability, etc.
Part Description	Thick Wall Heat Shrink provides excellent protection above or below ground level and is suitable for wet locations and direct burial (UL486D)
Material	Flame retardant polyolefin cross-linked with adhesive##
Color	Black
CSA Certified	Yes
Military Specification	AMS-DTL-23053/15 Class 1
UL Recognized	Yes
Length (In.)	9.00
Length (mm)	228.6
Copper Conductor Size Range	#3/0 - #400 MCM
Conductor Size Range (mm)	95 – 185
Flammability Rating	Flame Retardant
Max. Connector O.D. (In.)	1.190
Max. Connector O.D. (mm)	30.2
Max. Recovered I.D. (In.)	.50
Max. Recovered I.D. (mm)	12.7
Min. Cable O.D. (In.)	.600
Min. Cable O.D. (mm)	15.2
Min. Expanded I.D. (In.)	1.50
Min. Expanded I.D. (mm)	38.1
Nominal Recovered Wall Thickness (In.)	.170
Nominal Recovered Wall Thickness (mm)	4.3
Pricing Description	Heat Shrink Thick Adhesive, 1.5" (38.1mm) Dia, Black
Shrink Ratio	3:1
Temperature Range	-85°F to 230°F (65°C to 110°C)
Min. Order UOM	PC
Min. Order Qty.	10
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.