



Current refinements (click to remove)

Search Tips

Region USA Product Family HSTT Heat Shrink Bulk Reels Text Search: 'HSTT09-MC'

Your search criteria matched only one product, shown below.



Flexible Ployolefin DRYSHRINK™Heat Shrink Tubing

- General Purpose heat shrink tubing for dry locations
- Applications include insulating, protecting, harnessing and identifying wires.
- Material Type: Crosslinked Polyolefin
- Shrink Ratio: 2:1
- Temperature Range:-67°F to 275°F (55°C to 135°C)
- Flammability Rating: Flame retardant EXCEPT clear
- Voltage: 600 V
- UL Recognized, CSA Certified
- Mil Spec: AMSDTL-23053/5 Class 1 (Colors) Class 2 (Clear)

Part Number:	HSTT09MC
RoHS Compliancy Status:	Compliant
Part Description:	Thin Wall Polyolefin Heat Shrink
Material:	Polyolefin cross-linked
Color:	Clear
Military Specification:	AMS-DTL-23053/5 Class 2
Length Per Reel (ft.):	1000
Length Per Reel (m):	304.8
Max. Recovered I.D. (In.):	.046
Max. Recovered I.D. (mm):	1.2
Min. Expanded I.D. (In.):	.093
Min. Expanded I.D. (mm):	2.4
Nominal Diameter / Size:	.093
Nominal Recovered Wall Thickness (In.):	.020
Nominal Recovered Wall Thickness (mm):	.5
Shrink Ratio:	2:1
Temperature Range:	-67°F to 275°F (55°C to 135°C)
Min. Order UOM:	RL
Min. Order Qty.:	1
BOM Qty. (# of Pkgs.)	0
Add to My Catalog	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.