



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor


Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'HSTTK100-48-5'

Your search criteria matched only one product, shown below

HSTTK100-48-5



- For dry locations
- Semi-rigid, highly heat resistant
- Offers excellent chemical and abrasion resistance
- Use in high temperature or solvent rich environment
- Semi-rigid highly heat resistant
- Excellent chemical and abrasion resistance
- Meets AMS-DTL-23053/8
- Meets UL224 VW-1 flame retardant

Part Number	HSTTK10048-5
RoHS Compliancy Status	Compliant
Part Description	Semi-rigid heat resistant Kynar* Heat Shrink offers excellent chemical resistance in solvent rich environments.
Material	Kynar*
Color	Clear
CSA Certified	Yes
Military Specification	AMS-DTL-23053/8
UL Recognized	E122770
Length (ft.)	4
Length (m)	1.2
Flammability Rating	UL224 VW-1
Max. Recovered I.D. (In.)	.500
Max. Recovered I.D. (mm)	12.7
Min. Expanded I.D. (In.)	1.00
Min. Expanded I.D. (mm)	25.4
Nominal Diameter (In.)	1.00
Nominal Diameter (mm)	25.4
Nominal Recovered Wall Thickness (In.)	.019
Nominal Recovered Wall Thickness (mm)	0.5
Pricing Description	Heat Shrink Thin Kynar*, 1"(25.4mm) Dia
Shrink Ratio	2:1
Temperature Range	-67°F to 347°F (55°C to 175°C)
Min. Order UOM	PC
Min. Order Qty.	5
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.