



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'HSTTT43-48-Q'

Your search criteria matched only one product, shown below

HSTTT43-48-Q



- Applications include insulating, protecting, and color coding wires and cables
- Widest temperature range of any plastic material
- Voltage: 600V
- Shrink ratio: 2:1
- Mil Spec: AMSDTL-23053/12 Class 3
- Temperature range: -400°F to 500°F (-240°C to 260°C)
- Color: Opaque
- For dry locations
- Material: Polytetrafluroethylene (PTFE)

|                                        |                                                                                                                   |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Part Number                            | HSTTT4348-Q                                                                                                       |
| RoHS Compliancy Status                 | Compliant                                                                                                         |
| Part Description                       | Semi-rigid highly heat resistant Teflon* Heat Shrink offers widest temperature range of any heat shrink material. |
| Material                               | TFE Teflon*                                                                                                       |
| Color                                  | Milky clear                                                                                                       |
| CSA Certified                          | No                                                                                                                |
| Military Specification                 | AMS-DTL-23053/12 Class 3                                                                                          |
| Length (ft.)                           | 4                                                                                                                 |
| Length (m)                             | 1.2                                                                                                               |
| Flammability Rating                    | Flame Retardant                                                                                                   |
| Max. Recovered I.D. (In.)              | .278                                                                                                              |
| Max. Recovered I.D. (mm)               | 7.0                                                                                                               |
| Min. Expanded I.D. (In.)               | .430                                                                                                              |
| Min. Expanded I.D. (mm)                | 10.9                                                                                                              |
| Nominal Diameter / Size                | 2 AWG                                                                                                             |
| Nominal Recovered Wall Thickness (In.) | .015                                                                                                              |
| Nominal Recovered Wall Thickness (mm)  | .4                                                                                                                |
| Pricing Description                    | Heat Shrink Thin, Teflon, 2 AWG Dia, Clear                                                                        |
| Shrink Ratio                           | 2:1                                                                                                               |
| Temperature Range                      | -88°F to 482°F (-67°C to 250°C)                                                                                   |
| Min. Order UOM                         | PC                                                                                                                |
| Min. Order Qty.                        | 25                                                                                                                |
| BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>                                                                                    |
| Add to Favorite Product List           |                                                                                                                   |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.