

Current refinements (click ☐ to remove) Search Tips

☒ Region **USA** ☒ Product Family **HSTTV Heat Shrink 6 In. Pieces** ☒ Text Search: 'HSTTV12 -Y'

Your search criteria matched only one product, shown below.



- Small package fits easily in tool box
- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes
- Cross-linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
- Available in various colors for permanent, cost effective color coding

Meets Mil Spec AMSDTL-23053/5 Class 3.

Part Number:	HSTTV12-Y
RoHS Compliancy Status:	Compliant
Part Description:	Thin Wall Polyolefin Heat Shrink (UL224 VW-1)
Product Type:	Heat Shrink
Material:	Highly flame retardant polyolefin cross-linked**
Color:	Black
CSA Certified:	Yes
Military Specification:	AMS-DTL-23053/5 Class 3
UL Recognized:	E122770
Length (In.):	6.00
Length (mm):	152.4
Flammability Rating:	UL224 VW-1
Max. Recovered I.D. (In.):	.062
Max. Recovered I.D. (mm):	1.6
Min. Expanded I.D. (In.):	.125
Min. Expanded I.D. (mm):	3.2
Nominal Diameter (In.):	.125
Nominal Diameter (mm):	3.2
Nominal Recovered Wall Thickness (In.):	.020
Nominal Recovered Wall Thickness (mm):	0.5
Pieces per Package:	20
Shrink Ratio:	2:1
Temperature Range:	-67°F to 257°F (-55°C to 125°C)
Min. Order UOM:	PK
Min. Order Qty.:	1
BOM Qty. (# of Pkgs.)	0
Add to My Catalog	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.