



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
- PDFPan-Ty Bow-T ..
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'PLB4S-M39'

Your search criteria matched only one product, shown below

PLB4S-M39



- For high temperature applications up to 239°F (115°C) – indoor use
- A fast and economical method to secure and separate two bundles
- Reduces part number inventory – single part covers multiple bundle sizes
- Installs easily by hand – second loop can be installed with *PANDUIT* cable tie installation tools

Part Number	PLB4S-M39
RoHS Compliancy Status	Compliant
Part Description	Double Loop Cable Tie, 14.8", Standard cross section
Product Type	Cable Ties
Material	Heat Stabilized Nylon 6.6
Color	Natural
CSA Certified	Yes
UL Listed (File #E56854)	No
UL Recognized (File #E56854)	Yes
Length (In.)	14.8
Length (mm)	376
Width (In.)	.190
Width (mm)	4.8
CE Compliant	Yes
Cross Section	Standard
Head Height (In.)	.220
Head Height (mm)	5.6
Head Length (In.)	.465
Head Length (mm)	11.8
Head Width (In.)	.337
Head Width (mm)	8.6
Locking Style	Locking
Material Flammability Rating	UL 94V-2
Max. Combined Bundle Dia. (In.)	4.10
Max. Combined Bundle Dia. (mm)	104
Max. Continuous Use Temperature	239°F (115°C)
Min. Loop Tensile Strength (Lbs.)	50
Min. Loop Tensile Strength (N)	222
Pricing Description	Double Loop Tie, 14.8"L (376mm), Standard, Heat Stabilized, Natural
Thickness (In.)	.052
Thickness (mm)	1.3
Tool	GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2
Min. Order UOM	PC
Min. Order Qty.	1000
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.