



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
 - PDFMetric Ring ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) [Within Results](#)

Text Search: 'PM6-4R-X'

Your search criteria matched only one product, shown below

PM6-4R-X



- Ring tongue design assures a secure connection in high vibration applications
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Brazed seam protects terminal barrel from splitting during the crimp process
- Barrel of terminal internally beveled to provide quick and easy wire insertion
- Maximum recommended operating temperature 302°F (150°C)

	Part Number	PM64R-X
	RoHS Compliancy Status	Compliant
	Part Description	Metric ring terminal, 2.5– 6.0mm ² wire range, M4 stud size, non-insulated.
	Product Type	Terminals- Metric
	Length (mm)	19.8
	Width (mm)	7.9
	Clearance	7.9
	Pricing Description	Metric Ring Terminal, norinsulated, 2.5– 6.0mm ² wire range, M4 stud size
	Stud Size	M4
	Tool	CT-1570, CT-2500
	Wire Range (mm ²)	2.5 – 6.0
	Min. Order UOM	PC
	Min. Order Qty.	10
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.