




[Back to Result](#)

FTD83-14-C [Add to BOM](#) | [Add to Favorites](#)



Polypropylene insulated ferrules – twin wire DIN end sleeve.

Product Details	Related Documents
Std. Pallet Weight (lb)	0.0000
Std. Pkg. Qty.	100
Std. Ctn. Weight (lb)	0.0000
Std. Ctn. Volume (cf)	0.0000
Std. Pallet Volume (cf)	0.000000
RoHS Compliance Status	Compliant
Part Description	Polypropylene insulated ferrules – twin wire DIN end sleeve.
Color	Red
Length (mm)	26.0
Length (In.)	1.02
Pin Length (mm)	14.0
Wire Strip Length (mm)	19.6
CE Compliant	No
Wire Strip Length (In.)	25/32
Pin Length (In.)	0.55
Wire Range (mm²)	10.0
Wire Range	8 AWG
Pricing Description	Insulated Ferrule, twin wire, 8 AWG (10.0mm²), 0.55"(14.0mm) pin length, red DIN end sleeve
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Inside Diameter (mm)	6.5
Inside Diameter (In.)	0.26
Tool	CT-1005
Max. Wire Insul. Dia. (In.)	0.28
Max. Wire Insul. Dia. (mm)	7.0
Insulation	Polypropylene
Min. Order Qty.	100.0000