



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
  - PDFNon-Shrink P ..
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips € Within Results

Text Search: 'TV105-1M20Y'

Your search criteria matched only one product, shown below

TV105-1M20Y



- Non-Shrink oil resistant flexible clear tubing on reel
- Provides insulation and protection for lead wires wire harness assemblies soldered joints and components in electrical and electronic equipment
  - Material: Polyvinyl chloride (PVC)
  - Voltage Rating: 300V and 600V
  - All purpose flexible non -shrinkable
  - Resistant to heat and moisture
- Applicable Specifications:
- UL224 VW-1
  - CSA C22.2 No. 198.1 (OFT)
  - ASTM D-922 Grade CFR
  - MIL-I-631 Type F, Form U, Grade C- Class 1 Category 1

|                               |                                           |
|-------------------------------|-------------------------------------------|
| Part Number                   | TV105-1M20Y                               |
| RoHS Compliance Status        | Compliant                                 |
| Note                          | TV105-1M20Y replaces TV105-2TL20Y         |
| Part Description              | PVC NonShrink Tubing, 105°C rated         |
| Material                      | Polyvinyl Chloride                        |
| Color                         | Black                                     |
| CSA Certified                 | Yes                                       |
| CSA Specification             | CSA C22.2 No. 198.1 (OFT)                 |
| UL Recognized                 | E122770                                   |
| UL Recognized Specification   | UL224 VW-1                                |
| Flammability Rating           | UL224 VW-1                                |
| Length Per Reel (ft.)         | 1000                                      |
| Length Per Reel (m)           | 304.8                                     |
| Max. Inside Diameter (In.)    | .311                                      |
| Max. Inside Diameter (mm)     | 7.89                                      |
| Max. Voltage Rating           | 300 V                                     |
| Min. Inside Diameter (mm)     | 7.34                                      |
| Minimum Inside Diameter (In.) | .289                                      |
| Nominal Size                  | 1 AWG                                     |
| Pricing Description           | Vinyl Tubing, 1 AWG (8.81mm), 300V, Black |
| Temperature Range             | -4°F to 221°F (20°C to 105°C)             |
| Wall Thickness (In.)          | .020                                      |
| Wall Thickness (mm)           | .51                                       |
| Min. Order UOM                | RL                                        |
| Min. Order Qty.               | 1                                         |
| BOM Qty. (# of Pkgs.)         | <input type="text" value="0"/>            |
| Add to Favorite Product List  | €                                         |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.