Search Results

Evaluate
- FAQ's
Design a Solution
- Part Drawings
- PDF Dynamic Cabl..
- Specification Sheets
- PDF High Bond Ad..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ Text Search: 'ABDCM30-AV-C'

Your search criteria matched only one product, shown below

ABDCM30-AV-C

- High bond adhesive provides maximum adhesion, especially in harsh, high temperature, outdoor environments; extending service life
- Smooth surfaces and rounded edges protect the cable bundle and the installer; improving productivity, job site safety, and reliability
- Flexible, lightweight material is easily handled; improving productivity

Part Number	ABDCM30-AV-C
RoHS Compliancy Status	Compliant
Part Description	High Bond Dynamic Cable Manager for Panel Strain Relief
Material	Nylon 6.6
Color	White
Height (In.)	0.66
Height (mm)	16.8
Length (In.)	1.12
Length (mm)	28.4
Width (In.)	1.12
Width (mm)	28.4
Adhesive Type	VHB
Mounting Method	VHB Adhesive Tape
Overall Size W x H (In.)	1.98 x 0.66
Overall Size W x H (mm)	50.3 x 16.8
Pricing Description	Dynamic Cable Manager, VHB Adh, 1.12" x 1.12" (28.4mm x 28.4mm), Nylon 6.6, Nat
Temperature Range	-31°F – 185°F (-35°C – 85°C)
Used With Cable Ties	M, I, S
Min. Order UOM	PC
Min. Order Qty.	100
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2010, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy