

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFJP75DW____ P
- How to Buy
 - Bill of Material
 - Favorite Products Lis
 - Locate Distributor

Current refinements (click to remove) Search Tips

Text Search: 'JP75DW-L6'

Your search criteria matched only one product, shown below



- Complete horizontal and vertical 1" bend radius control helps prevent degradation of cable performance
- UL 2043 and CAN/ULC S102.2 listed and are suitable for use in air handling spaces
- Durable non-metallic J Hook materials provide the ability to manage and support a large number of cables
- Pre-riveted assemblies allow for attachment to ceilings, beams, threaded rods, drop wires and under floor supports to meet requirements of a variety of applications
- Wide cable support base prevents pinch points that could cause damage to cables
- Cable tie channel allows user to easily install 3/4" Tak -Ty® Cable Ties to retain cable bundle

Part Number	JP75DWL6
RoHS Compliancy Status	RoHS directive is not applicable
Part Description	J Hook with clip for use with #12 wire, threaded rod up to 1/4" (6.4mm) in diameter, or 1/8"–1/4" (3.2mm– 6.4mm) thick flanges.
Material	Nylon 6.6 J Hook with metal attachments
Color	Blue
10Gig (.33")	6
CAT 5E (.193")	11
CAT 6 (.248")	6
CAT 6Plus (.26")	4
CE Compliant	No
Max. Bundle Capacity (In.)	0.75
Max. Bundle Capacity (mm)	19.0
Max. Static Load (Kg)	4.53
Max. Static Load (Lbs.)	10
Pricing Description	J-Pro Cable Support System Drop Wire And Threaded Rod Clip
Min. Order Qty.	50
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.