



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'PUM-071-4S-D30'

Your search criteria matched only one product, shown below

PUM-071-4S-D30



	Part Number	PUM071-4S-D30
	RoHS Compliancy Status	Compliant
	Part Description	Fir Tree Push Mount Assembly
	Material	Heat Stabilized Nylon 6.6
	Color	Black
	Environment	Indoor
	Head Diameter (In.)	.67
	Head Diameter (mm)	17.0
	Mounting Method	Fir Tree Push Barb
	Overall Height (In.)	.67
	Overall Height (mm)	16.9
	Panel Hole Diameter Range (In.)	.25 - .28
	Panel Hole Diameter Range (mm)	6.3 - 7.1
	Panel Thickness Range (In.)	.03 - .28
	Panel Thickness Range (mm)	0.8 - 7.0
	Panel to Top of Mount (In.)	.26
	Panel to Top of Mount (mm)	6.6
	Pricing Description	Fir Tree Push Mount Assembly, .25".28" (6.3mm- 7.1mm) Panel Hole Di Range, HSBL
	Min. Order UOM	PC
	Min. Order Qty.	500
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.