

Search Results

- Evaluate
- FAQ's
- Design a Solution
- Catalog Cut Sheet
  - PDFPV18-4RX-CY
  - PDFPV14-8RX-C P
- How to Buy
- Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'PV14-14RX-L'

Your search criteria matched only one product, shown below

PV14-14RX-L



- Expanded wire entry designed to accommodate wire with a larger insulation thickness
  - Ring tongue design assures a secure connection in high vibration applications
  - Insulation support helps to prevent wire damage in bending applications
  - Brazed seam protects terminal barrel from splitting during the crimp process
  - Internal barrel serrations assure good wire contact and maximum tensile strength
  - UL Flammability UL 94V -0, maximum insulation temperature 221°F (105°C)
  - UL and CSA rated up 600 V per UL 486A/B
- ‡UL and CSA approved tooling/product combinations.

|                               |                                                                                                     |
|-------------------------------|-----------------------------------------------------------------------------------------------------|
| Part Number                   | PV14-14RX-L                                                                                         |
| RoHS Compliance Status        | Compliant                                                                                           |
| Note                          | PV14-14RX-L replaces PV14-14RX-C                                                                    |
| Part Description              | Ring Terminal, 16- 14 AWG, 1/4" stud size, vinyl insulated, expanded insulation for large wire O.D. |
| Product Type                  | Terminals                                                                                           |
| CSA Certified                 | Yes                                                                                                 |
| UL Listed                     | Yes                                                                                                 |
| Length (In.)                  | 1.16                                                                                                |
| Length (mm)                   | 29.5                                                                                                |
| Width (In.)                   | 0.46                                                                                                |
| Width (mm)                    | 11.7                                                                                                |
| CE Compliant                  | No                                                                                                  |
| Clearance                     | 0.37                                                                                                |
| Clearance (mm)                | 9.4                                                                                                 |
| Insulation                    | Vinyl                                                                                               |
| Max. Ins.                     | 0.200                                                                                               |
| Max. Ins. (mm)                | 5.1                                                                                                 |
| Panduit Color Code            | Blue                                                                                                |
| Plating Type                  | Tinned                                                                                              |
| Pricing Description           | Ring Terminal, expanded vinyl insulation, 16 14 AWG, 1/4" stud size                                 |
| Stock                         | 0.03                                                                                                |
| Stock (mm)                    | 0.8                                                                                                 |
| Stud Hole Size (mm)           | M6                                                                                                  |
| Stud Size                     | 1/4"                                                                                                |
| Temperature Rating            | 221 Degrees Fahrenheit (105 Degrees Celsius)                                                        |
| Tool                          | CT-100A‡, CT-600-A‡, CT -1550‡, CT-1551‡, CT-2500‡                                                  |
| Wire Range                    | 16 – 14 AWG                                                                                         |
| Wire Range (mm <sup>2</sup> ) | 1.5 – 2.5                                                                                           |
| Min. Order UOM                | PC                                                                                                  |
| Min. Order Qty.               | 50                                                                                                  |
| BOM Qty. (# of Pkgs.)         | <input type="text" value="0"/>                                                                      |
| Add to Favorite Product List  |                  |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.