

[support](#) | [locate distributor](#) | [about panduit](#) | [careers](#) | [worldwide](#)*World Leader in Network and Electrical Solutions*[Printer Friendly](#)[HOME](#) | [SOLUTIONS](#) | [RESOURCES](#) | [PRODUCTS](#) | [SERVICES](#) | [LEARNING](#)

SEARCH

Current refinements (click ☒ to remove)[Search Tips](#) ☒ [Region](#) ▶ [USA](#) ☒ [Product Family](#) ▶ [Braided Expandable Sleeving – Polyethylene Terephthalate \(PET\)](#) ☒ [Text Search: 'SE75P-DR10'](#)**Your search criteria matched only one product, shown below.**

- Provides continuous abrasion resistance for wires cables and tubing
- Lightweight durable protection
- Highly flexible open weave will not trap heat or humidity
- Rated for use up to 257°F (125°C)
- Allows for use with irregular shapes
- Stock colors: Black gray and white

Part Number:	SE75P-DR10
RoHS Compliancy Status:	Compliant
Part Description:	Braided Expandable Sleeving provides continuous abrasion resistance for wires, cables and tubing. The highly flexible open weave will not trap heat or humidity.
Material:	Polyethylene Terephthalate
Color:	White
CSA Certified:	Yes
UL Recognized:	E116868
Length (ft.):	500
Length (m):	152.4
Flammability Rating:	UL94 HB
Nominal Diameter Range (In.):	.500 to 1.25
Nominal Diameter Range (mm):	12.7 to 31.8
Nominal I.D. (In.):	.75
Nominal I.D. (mm):	19.1
Temperature Range:	-94°F to 257°F (-70°C to 125°C)
Min. Order UOM:	RL
Min. Order Qty.:	1
BOM Qty. (# of Pkgs.)	0
Add to My Catalog	☐

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2007, PANDUIT CORP. All rights reserved.