



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'UTPCH5BUY'

Your search criteria matched only one product, shown below

UTPCH5BUY



- Exceed ANSI/TIA/EIA568-B.2 Category 5e and ISO11801 Class D standards
- Meet draft requirements of IEEE 802.3at for PoE Plus
- Each patch cord is 100% performance tested and wired to T568A
- Constructed of Category 5e, 24 AWG UTP stranded cable and *Pan-Plug*® Modular Plugs; plug contacts plated with 50 microinches of gold for superior performance
- Plug meets all applicable ANSI/TIA -968-A requirements and exceeds IEC 60603 -7 specifications
- Patented tangle free latch prevents snags and provides easy release, saving time on frequent moves, adds, and changes
- Labels on patch cords provide identification of performance level, length, and quality control number
- Optional Patch Cord Color Bands snap on and off individual patch cables offering endless color-coding options
- Optional RJ45 Plug Lock -In Device blocks unauthorized removal of cable, IP phone, other

networking equipment or critical connection

- Third party tested to Category 5e component compliance

Part Number	UTPCH5BUY
RoHS Compliancy Status	Compliant
Note	UTPCH5BUY replaces UTPCH5BU
Part Description	Category 5e, UTP patch cord with PanPlug™ Modular Plugs on each end.
Product Type	Copper Patch Cord
Color	Blue
Length (ft.)	5
Length (m)	1.52
Boot Color	No Boot
Cable Color	Blue
Cable Type	UTP
CE Compliant	No
CE Marking	No
Connector 1 Type	Pan-Plug™ Modular Plug
Connector 2 Type	Pan-Plug™ Modular Plug
Flammability Rating	CM
Performance Level	Category 5e
Pricing Description	Copper Patch Cord, Category 5e, Blue UTP Cable, 5 Feet
Wiring Scheme	T568A
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.