

D-181 - 3222 - 90/9 Product Details

D-181 - 3222 - 90/9

TE Part Number: 024278 - 000

Active

Add to Part List

Shield Terminators

Always ELV Compliant

(

Statement of Compliance

)

Product Highlights:

? Sealing = Splash Resistant

? Cable Temperature Rating = 125 °C

? Jacket Outer Diameter = 2.54 - 5.20 mm

? Shield O.D. (Min.) = 2.15 - 4.60 mm

? With Preinstalled Lead

View all Features

|

Find Similar Products

Quick Links

Check Pricing & Availability

Search for Tooling

Product Feature Selector

Contact Us About This Product

Documentation & Additional Information	
Product Drawings: ? Coaxial SolderSleeve Device with Pre -installed Lead (PDF, English) Catalog Pages/Data Sheets: ? None Available Product Specifications: ? None Available Application Specifications: ? None Available Instruction Sheets: ? None Available CAD Files: ? None Available	Additional Information: ? Product Line Information Related Products: ? Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Mechanical Attachment: ? Inside Diameter (mm [in]) = 5.20 [0.205] Body Related Features: ? Jacket Outer Diameter (mm [in]) = 2.54 - 5.20 [0.100 - 0.205] Housing Related Features: ? Sealing = Splash Resistant ? Shield O.D. (Min.) (mm [in]) = 2.15 - 4.60 [0.085 - 0.180] ? Preinstalled Lead = With ? Preinstalled Lead Wire Size (mm² [AWG]) = 0.38 [22] ? MIL or NAS Specification (MIL -S-83519) (NAS 1747) = No ? Length (Max.) (mm [in]) = 21.50 [0.850]	Configuration Related Features: ? Temperature Indication System = Without Industry Standards: ? RoHS/ELV Compliance = ELV compliant ? Lead Free Solder Processes = Not relevant for lead free process ? RoHS/ELV Compliance History = Always was ELV compliant Conditions for Usage: ? Cable Temperature Rating (°C) = 125 ? Operating Temperature (Max.) (°C) = 150 Other: ? Brand = Raychem