



[+ HARNESING](#)

SOLDERSLEEVE SHIELD TERMINATORS



✓ Active

TE CONNECTIVITY (TE)

CWT-13-W122-9

[Raychem](#) | [CBT](#) , [Terminator](#)

CWT-13-W122-9

TE Internal Number: 307083-000

Alias ID: 1192326-7

[Not EU RoHS Compliant](#)

[Not EU ELV Compliant](#)

Product Type Shield Terminator

Operating Temperature (Max) (°C) 125

Expanded Inside Diameter (Min) 13 mm [.51 in]

Pre-Installed Lead Yes

Resistance Properties Splash Protection

[↓](#) **PRODUCT DRAWING**
English

DOCUMENTATION

Product Drawings

SolderSleeve Terminator With Pre-Installed Lead

PDF

English

Product Specifications

Product Specification

SolderSleeve Insulated Electrical Termination Devices

PDF

English

SolderSleeve One-Step Wire And Cable Terminators Installation Procedures For CWT Products

PDF

English

Product Environmental Compliance

REACH Substance Communication Document

RSCD_Cadmium

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type Shield Terminator

Temperature Indicator No

Configuration Features

Pre-Installed Lead Yes

Pre-Installed Lead Type XL Polyethylene

Body Features

Shield Outside Diameter (Min) 8.9 mm [.35 in]

Lead Stranding Stranded

Lead Color White

Lead Plating Material Tin

Dimensions

Expanded Inside Diameter (Min) 13 mm [.51 in]

Overall Length 45.5 mm [1.79 in]

Pre-Installed Lead Wire Size (mm²) .38

Jacket Outside Diameter 13 mm [.51 in]

Usage Conditions

Operating Temperature (Max) (°C) 125

Resistance Properties Splash Protection

Wire Temperature (Max) (°C) 85

Industry Standards

MIL/NAS Specification (MIL-S-83519, NAS-1747) No

Government Qualified No

Statement of Compliance

Statement of Compliance

PDF