



Cable Clamps - Screw Mount, P Style -
Compatible Cable Diameter Range - 12.7 mm |
0.500 in ; Operating Temperature Range - -40 -
85 °C | -40 - 185 °F ; Black

Item code: 22CC37B0500B

In production

This screw down plastic P-clip that is easy to install. Ideal for holding cables, tubes or pipes.



.

[See all specs and customise](#)

Print page

Pricing and options

Standard pack: 4000
Order in multiple of 4000

Need a quote?

For large volumes and customised products, add to your cart and click request a quote, or email sales@essentracomponents.co.uk. Once received we will respond within 1 working day

Specifications

Imperial Metric

Adjustability	Fixed
Colour	Black
Fitting Style	Clamp
Material	Nylon
Mounting Method	Screw
Compatible Cable Diameter Range	12.7 mm
Hole Diameter	3.6 mm
Maximum Compatible Cable Diameter	12.7 mm
Maximum Operating Temperature	85 °C
Minimum Compatible Cable Diameter	12.7 mm
Minimum Operating Temperature	-40 °C

Operating Temperature Range	-40 - 85 °C
Overall Width	9.5 mm
Full Material	Nylon 6/6
Material Flammability Standard	UL94 V-2
Style	P Clip
Type	1

Useful Information

Documents



[22CC37B0500_Technical_Drawing](#)

Recommended Products



Flat Cable Clip - Two-Piece - Natural ;

[See our selection →](#)



Square Glide - Head Shape - Square Material - LDPE ; Colour - Grey

[See our selection →](#)



Nickel Steel Slotted Round Book Screw - Thread Length 6.0 mm | 0.2...

[See our selection →](#)



Round Tube Insert - 20.0 mm | 0.787 in Material - LDPE ; ...

[See our selection →](#)



[BACK TO TOP ^](#)

Information Legal Policies

[Contact Us](#)

[About Us](#)

[Sustainability](#)

[Catalogues](#)

[Delivery & Returns Information](#)

[Careers](#)

[Quality Statement](#)

[Conditions of Sale](#)

[Privacy Policy](#)

[Health and Safety](#)

[Modern Slavery](#)

[Statement](#)

Legal Policies

[Terms of Use](#)

[Cookie Policy](#)

[Promotion Terms](#)

[GDPR](#)

[Order Cancellation](#)

Contact Us

Tel: 0845 758 5070

Email: sales@essentracomponents.co.uk