



Contact Us: 800-847-0486

[Choose Country](#) |  **United States**

United States English

[Login or Register](#)

ESSENTRA

Search by SKU, Product Name or Keyword

SEARCH

CART



[Products](#)  [Catalogs](#) [Free Samples](#) [Free CAD](#) [Knowledge Center](#) [Contact Us](#)

[Home](#)

[Fiber, Wire & Cable Manage...](#)

[Cable Clips & Clamps](#)

[Wire Saddles](#)

[Wire Saddles - Mini](#)



Mini Wire Saddle, Natural,.30 in Spacer, UL94 V-0, .150 in Hole, .063 in Panel, .12 in x .26 in

Item Code: MWSELF-1-7.7-19

This miniature wire saddle snap locks into a .150 in (3.8 mm) diameter hole in a .063 in (1.6 mm) thick panel. The inside dimensions are .12 in (3 mm) x .26 in (6.6 mm). It has a .30 in (7.6 mm) spacer length. It is made is UL94 V-0 rated Nylon 6/6.

 In Stock 

Downloads



Print Page

Dependent Products

Recently Viewed



Mini Wire Saddle,
Natural,.30 in Spacer,
UL94 V-0, .150 in Hole,
.063 in Panel, .12 in x .26
in

ESSENTIAL SOLUTIONS

DELIVERED

Abrasives & Grinding
Access Hardware
Adhesives, Sealants & Tapes
Bearings & Power Transmissions
Caps & Plugs

Clamps & Workholdings
Cutting & Machining
Extrusions & Structural Systems
Fasteners
Feet, Casters & Glides

Fiber, Wire & Cable Management
Flange Protection
Knobs, Handles & Grips
Material Handling
Shop Supplies

PCB & Electronics Hardware
Pneumatics & Hydraulics
Raw Materials
Tamper Evident & Security Seals
Tooling & Positioning Components
Tools & Precision Instruments



About Us

[About Essentra Components](#)
[About Essentra PLC](#)
[Locations](#)
[Knowledge Center](#)

Customer Service

[Contact Us](#)
[Catalogs](#)
[Sample Program](#)
[Free CAD](#)
[Careers](#)
[Distributor Portal](#)

Policies

[Privacy Policy](#)
[Terms and Conditions of Sale](#)
[Terms and Conditions of Purchase](#)
[Environmental Policy](#)
[Health and Safety](#)
[Quality Statement](#)

Terms of Use

[Website Terms of Use](#)
[Cookie Policy](#)



ABOUT SSL CERTIFICATES

