

Pushbutton, 18.2 mm, screw terminal, momentary contact function, 1 NC + 1 NO, bezel white



fields of application

- Mechanical and system engineering
- Model construction
- Home technology

description

Pushbutton with mounting hole diameter 18.2 mm, non-illuminated, 250 V / 4 A

technical data

➤ general

illuminated	No
Bezel color	white
Collar shape	round
Operating temperature, min.	-25 °C
Operating temperature, max.	85 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	90 °C
Packaging	Box
Packaging unit	100 pcs.
net weight	16 g
Operating life	50,000 Cycles
Degree of protection, front side, according to DIN EN 60529	IP40 IP65 IP65 with sealing cap
RoHS compliant	Yes
REACH compliant	Yes

➤ mounting diameters

Mounting hole	18.2 mm
Mounting depth	34 mm

direct links

- [RAFI eCatalog](#)

Installation height 10.5 mm

Outside dimension, width 22 mm

➤ **mechanical data**

Actuation function momentary contact function

Operating force, min. 9.5 N

Operating travel, max. 5 mm

Contact function 1 NC + 1 NO

Contact system Bridge-sliding contact

Contact material Silver

Fixing Threaded ring

Terminal on the rear Screw terminal

➤ **electrical data**

Rated voltage, max. 250 V

Rated current, max. 2 A