

RAFIX 16, lamp socket W2 x 4.6d, quick-connect terminal, for W 2 x 4.6d



fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Industrial robots

description

technical data

➤ general

illuminated	Yes
Color	light gray
Operating temperature, min.	-25 °C
Operating temperature, max.	55 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	85 °C
Lamp socket	W 2 x 4.6d
Vibration-resistance according to standard IEC 60068-2-6	10 g at 20 - 500 Hz
Shock resistance according to standard IEC 60068-2-27	50 g at 11 ms amplitude semi-sinusoidal
Packaging unit	5 pcs.
net weight	1.8 g
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
RoHS compliant	Yes
REACH compliant	Yes

direct links

- [RAFI eCatalog](#)

➤ mounting diameters

Mounting depth	30.5 mm
Outside dimension, width	15.9 mm

Outside dimension, height 23.9 mm

> **mechanical data**

Fixing Latching

Terminal on the rear Flat quick-connect terminal 2.8 x 0.8

Lötbarkeit No

drawings

System drawing

