Back to Overview



ShareThis
Product Question

E-DAT modul 2 port AP pure white

- surface-mounted termination unit with E-DAT modul
- certified to GHMT Cat.6 de-embedded PVP
- compliance with class E_A to ISO/IEC 11801 Ed.2.2:2011-06, DIN EN 50173-1:2011-09
- tested: Link up to 500 MHz
- for 10 GBit Ethernet (IEEE 802.3an)
- suitable for Power over Ethernet (PoE, PoE plus and UPoE)
- easy to install connection of 2 to 4 pair data lines AWG 26/1 - 22/1 and stranded wires with 7 copper conductors AWG 26/7 to BTR 8-fold insulation displacement connectors (IDC)
- module plug direction 45° downwards
- strain relief with cable tie at the module
- with label window for enclosed identification labels
- label sheet 209 x 294 mm see accessory
- integrated dust protection covers (also colored)
- pearl white RAL 1013 or pure white RAL 9010 cover parts; structured surface with matt finish
- variants: 1 port, 2 ports, 3 ports
- color variants: pure white and pearl white

Technical Data
Accessories
Downloads

P/N	1309120002-E
Color	pure white
Feature 1	AP 2 Port
Feature 2	
EAN-No	4250184105640

last update on Wednesday, 30. July 2014 - 3:56