

Automation Technology > Industrial Communication > PROFIBUS > PROFIBUS Network components > Electrical networks (RS485) > RS 485 bus connector

6ES7972-0BA52-0XA0 PB CONNECTOR, 90 DEGREE, W/O PG SOCKET

Technical Data



SIMATIC DP,BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S 90 DEGREE ANGLE CABLE OUTLET, IPCD TECHNOLOGY FAST CONNECT, WITHOUT PG SOCKET 15,8 X 59 X 35,6 MM (WXHxD),

[nicht versorgt: PMD_ABS675_001_000]

-

9.6 kbit/s...12 Mbit/s

Interfaces

Number of electrical connections

-

2

- [nicht versorgt - für Netzkomponenten und Endgeräte]

1

Design of the electrical connection / [nicht versorgt - FastConnect]

Yes

Mechanical data

material / of the housing

plastic

Design, dimensions and weight

Width

15.8 mm

Height

59 mm

Depth

35.6 mm

net weight

10 g

Permitted ambient conditions

Ambient temperature

- during the operating phase
- during storage
- during transport

0 °C...60 °C

-40 °C...70 °C

-40 °C...70 °C

Relative humidity / at 25 °C / without condensation / during the operating phase / maximum

95 %

Protection class IP

IP20

Product properties, functions, components /

general

Product feature / [nicht versorgt - siliconfrei] Yes

Composant produit

- [nicht versorgt - PG-Anschlussbuchse] No
- décharge de traction Yes

Standards, specifications, approvals

[nicht versorgt: PMD_ABS586_001_000]

- Yes
- UL-registration Yes

letzte Änderung: May 9, 2011