

REV. Status

REVISION -
05/20/85 MS

REVISION A
GRD PIN
04/27/87 MS

REVISION B
REVISED AND
REDRAWN ON
CAD/CAM
04/24/98 TS


LOW PROFILE TELECOMMUNICATIONS TRANSFORMER 600:600 WITH SHIELD

A. Electrical Specifications (@ 25°C)


1. Pri Source Impedance; 600Ω
2. Sec Load Impedance; 600Ω Shielded
3. Pri DC Current; 0mA
4. Operating Level; -45dBm to +7dBm
5. Insertion Loss;
1.0dB MAX @ 1KHz, 0dBm, DC0mA
6. Frequency Response (relative to 1KHz);
±0.5dB @ 300Hz to 3.5KHz, 0dBm, DC 0mA
7. Pri Impedance; 600Ω ±15% @ 300Hz to 3.5KHz, 0dBm, DC 0mA
8. Longitudinal Balance; 60dB MIN @ 200Hz to 4KHz
9. DC Resistance;
(1-4) = 34Ω ±20%
(5-8) = 41Ω ±20%
10. Turns Ratio; (1-4) : (5-8) = 1 : 1.00 ±2%
11. Dielectric Strength;
2500Vrms 1 minute @ Pri to Sec, Core and Shield
2500Vrms 1 minute @ Sec to Shield
1000Vrms 1 minute @ Sec to Core

B. Marking; TTC-164, TAMURA, 196-date code, country of origin

C. Schematic Diagram




PIN 1 Designation




E. Mechanical Specifications;

All dimensions shown are nominal unless otherwise specified




4.3 ±1.0(0.17 ±0.04) 8 PLACES

Date code and country of origin



∅ 1.0(0.04) 8 PLACES



PREPARED BY:

D. Kelley

ENGINEER:

T. Shiozawa

QUALITY CONTROL:

D. Kelley

APPROVED:

D. Suzuki

DWG CONTROL NO.
P-A1-10133
ACAD\TTC\A1101331.DWG

REV
B

TELECOMMUNICATION COUPLING
TRANSFORMER

TAMURA CORPORATION OF AMERICA

43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
(909) 699-1270 FAX 9096769482

TTC-164

MODEL SPECIFICATION

DIM: mm(In) SCL: 1/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.

MODEL NUMBER

TTC-164