

Family

Catalog Number: F4000

**Product ID:** 7TAI029790R0027 **UPC Number:** 78621033668

Status: A

Polypropylene-Insulated Old DIN Ferrule, Total Length .571 Inches/14.5mm, Pin Length .315 Inches/8mm, Pin Diameter .043 Inches/1.1mm, Base Diameter .102 Inches/2.6mm, Wire Range #20 AWG/.50mm2, Color Orange, Copper, Tin Plated

- Ferrules ensure reliable electrical connections when terminating conductors in screw clamp terminal blocks.
- Application Tools: T1, T3, ERG4

North American Specifications (UNSPSC)	
UNSPSC	39121432 Electrical terminals
IGCC	4603 Electrical terminals
Brand Name	Sta-Kon
Туре	Ferrule
Special Features	Ferrules ensure reliable electrical connections when
	terminating conductors in screw clamp terminal
	blocks.
Standard	UL E489056
Wire Size	20 AWG
Material	Copper
Color	Orange

European Specifications (ETIM)	
ETIM	EC000005 Cable end sleeve
Construction type	Standard
Nominal cross section	0.5mm²
Insulated	Υ
Insulation material	Polypropylene
Colour	Orange
Material	Copper
Surface protection	Tinned
With identification flag	N
Reel packaging	N

Packaging	
Inner Quantity	500
Outer Quantity	10000
Outer Dimensions (inches)	6.5x4.5x4
Weight Uom	0.63 lbs. per 1000

## **Documents / Support Tools**

Technical Drawing / Data Sheet WSD-000402

## For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50

860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com