

L-14-120MH-0-C

All-plastic cable tie with mounting head. UV-resistant version, especially recommended for outdoor applications.

Catalog Number:	L-14-120MH-0-C
EAN Number:	05414363025559
UPC Number:	72849491140
Description:	All-plastic, integrated mounting hole cable tie, 382 x 7.6 mm, black Polyamide 6.6 UV-resistant



Technical Information	
Type	integrated mounting hole
Material	Polyamide 6.6 UV-resistant
Temperature Range	-40°C to +85°C
Flammability Rating	UL 94 V-2
Colour	black
Halogen free	yes
Silicone free	yes
UV-resistant	yes
Approvals	
UL recognised	E49405
Ordering Information	
Length (mm)	382
Width (mm)	7.6
Max. Bundle Diameter (mm)	102
Min. Bundle Diameter (mm)	5
Min. Tensile Strength (N)	540
Diameter of Mounting Hole (mm)	M6
Quantity (pieces)	100
Packaging Type	bag
Storage Conditions	Nylon (Polyamide) is inherently susceptible to environmental conditions. Polyamide 6.6 cable ties are moisturised to optimum performance levels at machine-side and should be stored in cool dry areas out of direct sunlight. Cable ties are packaged in plastic bags to contain moisture and should remain sealed until ready for use.
Tooling	ERG120, L-500-EU, WT3D