



Main

Range of product	Osiswitch
Series name	Universal
Device short name	ZCP
Body type	Fixed
Number of poles	2

Complementary

Design	Compact
Body material	Plastic
Contacts insulation form	Zb
Contacts material	Silver plated contacts
Minimum actuation speed	0.01 m/min
Contact code designation	B300, AC-15 (Ue = 240 V, Ie = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A R300, DC-13 (Ue = 250 V, Ie = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A
Ui rated insulation voltage	300 V conforming to CSA C22-2 No 14 300 V conforming to UL 508 500 V degree of pollution 3 conforming to IEC 60947-1
Resistance across terminals	< 25 mOhm conforming to IEC 60255-7 category 3
Uimp rated imp wstdvoltage	6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1
Short circuit protection	10 A by gG cartridge fuse
Electrical durability	5000000 cycles, DC-13 (Uc = 120 V) , 4 W, load factor: 0.5, operating rate: < 60 cyc/mn conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 (Uc = 24 V) , 10 W, load factor: 0.5, operating rate: < 60 cyc/mn conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 (Uc = 48 V) , 7 W, load factor: 0.5, operating rate: < 60 cyc/mn conforming to IEC 60947-5-1 appendix C
Width	31 mm
Height	65 mm
Depth	30 mm
Product weight	0.07 kg
Terminals description ISO nT1	(13-14)NO (21-22)NC

Environment

Product or component type	Limit switch body
Product compatibility	XCKD
Associated head	ZCE01 ZCE02 ZCE06 ZCE07 ZCE08 ZCE09 ZCE10 ZCE11 ZCE13 ZCE14 ZCE21 ZCE24 ZCE27 ZCE28 ZCE29 ZCE62 ZCE63 ZCE64 ZCE65 ZCE66 ZCE67 ZCEH0 ZCEH2
Electrical connection	M12 male connector, 4 pins
Contacts type and composition	1 NO + 1 NC
Contacts operation	Snap action
Positive opening	With
Ambient air temp for storage	-40...70 °C