



## Main

|                             |                                                                                                                                   |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Range of product            | Harmony XALD                                                                                                                      |
| Product or component type   | Empty control station                                                                                                             |
| Device short name           | XALD                                                                                                                              |
| Product destination         | For XB5 Ø 22 mm control and signalling units                                                                                      |
| Number of cut-out           | 1 cut-out                                                                                                                         |
| Colour of base of enclosure | Light grey RAL 7035                                                                                                               |
| Colour of cover             | Dark grey RAL 7016                                                                                                                |
| Material                    | Polycarbonate                                                                                                                     |
| Cable entry                 | 2 knock-outs for Pg 13 cable gland and ISO M20, clamping capacity: 12 mm<br>1 knock-out for cable entry, clamping capacity: 14 mm |
| IP degree of protection     | IP69<br>IP67<br>IP66 conforming to IEC 60529<br>IP69K                                                                             |

## Complementary

|                                    |                                                                    |
|------------------------------------|--------------------------------------------------------------------|
| Assembly style                     | For customer assembly                                              |
| Number of horizontal rows          | 1                                                                  |
| Number of vertical rows            | 1                                                                  |
| Product weight                     | 0.136 kg                                                           |
| Resistance to high pressure washer | 7000000 Pa at 55 °C, distance: 0.1 m                               |
| Mounting of block                  | Front mounting<br>Rear mounting                                    |
| Electrical composition code        | SR1<br>SR2<br>MR1<br>MF1<br>PF1<br>MF2<br>PF2<br>SF1<br>SF2<br>PR1 |

|                  |               |
|------------------|---------------|
| Main group       | 1 cut-out     |
| Group of product | Standard grey |

## Environment

|                                       |                                                                                                                       |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TH                                                                                                                    |
| Ambient air temperature for storage   | -40...70 °C                                                                                                           |
| Ambient air temperature for operation | -40...70 °C                                                                                                           |
| Overvoltage category                  | Class II conforming to IEC 60536                                                                                      |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                                                                    |
| IK degree of protection               | IK03 conforming to EN 50102                                                                                           |
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>JIS C 4520<br>UL 508<br>CSA C22.2 No 14 |

## Offer Sustainability

|                                  |                                                                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                                                                 |
| RoHS (date code: YYWW)           | Compliant - since 1422 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available<br><a href="#">Product Environmental Profile</a>                                                                            |
| Product end of life instructions | Need no specific recycling operations<br><a href="#">End of Life Information</a>                                                      |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|