# Product data sheet Characteristics

## XVBC21

Base unit + cover for modular tower lights, plastic, black, Ø70, bottom entry, side cable entry





#### Main

Range of product	Harmony XVB Universal	
Product or component type	Base unit with cover	
Component name	XVBC	
Material	Glass reinforced polyamide: base unit Polycarbonate: cover unit	

## Complementary

Fixing mode	Direct or tube fixing	
Mounting diameter	70 Mm	
Product destination	Banks without flash discharge tube unit	
Electrical connection	1 connector for standard input	
Cable entry	Bottom or side entry	
Assembly style	Customer assembly, up to 5 units	
Terminals description ISO n°1	(GND)GROUND (COM-1)PW (COM-4)PW (COM-3)PW (COM-5)PW (COM-2)PW	
Net weight	0.19 Kg	

#### **Environment**

Product certifications	CCC UL 508 GOST CSA C22-2 No 14	
Standards	EN/IEC 60947-5-1	
Protective treatment	TC	
Ambient air temperature for storage	-4070 °C	
NEMA degree of protection	NEMA 4X conforming to UL 508 (indoor)	

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	199 G
Package 1 Height	8.5 Cm
Package 1 width	10 Cm
Package 1 Length	9.5 Cm
Unit Type of Package 2	S03
Number of Units in Package 2	36
Package 2 Weight	7.877 Kg
Package 2 Height	30 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm
Unit Type of Package 3	P06
Number of Units in Package 3	288
Package 3 Weight	71.516 Kg
Package 3 Height	77 Cm
Package 3 width	80 Cm
Package 3 Length	60 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	☐ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

### Contractual warranty

Warranty	18 months

Product Life Status : Commercialised