

## Waber-by-Tripp Lite 6-Outlet Industrial Surge Protector, 6-ft. Cord, 1050 Joules

MODEL NUMBER: DG206



### Highlights

- 6 outlets/6 ft. cord
- 1050 joule rating

### Package Includes

- DG206 Power Strip
- Warranty information
- Instruction manual

### Description

The Waber-by-Tripp Lite DG206 Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built in surge suppression rated at 1050 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive gray color scheme.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded metal power distribution strip with lighted power switch

SUPPRESSION - 1050 joules AC suppression

### Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tabs for installation in a wide variety of applications
- UL1449 (USA/400V rating), UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

## Specifications



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

| OVERVIEW                           |                                                                                    |
|------------------------------------|------------------------------------------------------------------------------------|
| UPC Code                           | 037332101020                                                                       |
| OUTPUT                             |                                                                                    |
| Frequency Compatibility            | 50 / 60 Hz                                                                         |
| Output (Watts)                     | 1800                                                                               |
| Output Receptacles                 | (6) 5-15R                                                                          |
| Circuit Breaker (amps)             | 15                                                                                 |
| Transformer Accommodation          | (2) Yes                                                                            |
| Right-Angle Outlets                | No                                                                                 |
| INPUT                              |                                                                                    |
| Nominal Input Voltage(s) Supported | 120V AC                                                                            |
| Recommended Electrical Service     | 120V (110-125V)                                                                    |
| Input Cord Gauge Type              | 14 gauge; SJT                                                                      |
| Voltage Compatibility (VAC)        | 120                                                                                |
| Maximum Surge Amps                 | 19500                                                                              |
| Input Plug Type                    | NEMA 5-15P                                                                         |
| Input Cord Length (ft.)            | 6                                                                                  |
| Right-Angle Plug                   | No                                                                                 |
| Input Cord Length (m)              | 1.83                                                                               |
| Integrated Cord Clip               | No                                                                                 |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                    |
| Diagnostic LED(s)                  | Yes                                                                                |
| Switches                           | Lighted two position power switch controls power to all outlets                    |
| Diagnostic LED Details             | Protection present (green)                                                         |
| SURGE / NOISE SUPPRESSION          |                                                                                    |
| AC Suppression Joule Rating        | 1050                                                                               |
| AC Suppression Response Time       | < 1 ns                                                                             |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| UL1449 Let Through Rating          | 400V - UL Verified                                                                 |
| Immunity                           | Conforms to IEE 587 / ANSI C62.41                                                  |
| Automatic Shut-Off                 | Yes                                                                                |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| DATALINE SURGE SUPPRESSION          |                           |
|-------------------------------------|---------------------------|
| Telephone/DSL Protection            | No                        |
| Cable (Coax) Protection             | No                        |
| Network (Ethernet) Protection       | No                        |
| PHYSICAL                            |                           |
| Anti-Microbial Protected            | No                        |
| Color                               | Light Gray                |
| Color (AC Line Cord)                | Light Gray                |
| Integrated Keyhole Mounting Slots   | Yes                       |
| Material of Construction            | Metal                     |
| Receptacle Color                    | White                     |
| Shipping Dimensions (hwd / cm)      | 6.10 x 14.48 x 36.58      |
| Shipping Dimensions (hwd / in.)     | 2.40 x 5.70 x 14.40       |
| Shipping Weight (kg)                | 0.91                      |
| Shipping Weight (lbs.)              | 2.00                      |
| Unit Dimensions (hwd / cm)          | 3.175 x 6.35 x 31.12      |
| Unit Dimensions (hwd / in.)         | 1.25 x 2.5 x 12.25        |
| Unit Weight (kg)                    | 1.09                      |
| Unit Weight (lbs.)                  | 2.4                       |
| SPECIAL FEATURES                    |                           |
| Rotatable Outlets                   | No                        |
| CERTIFICATIONS                      |                           |
| UL1449 3rd Edition (AC Suppression) | UL1449 3rd Edition        |
| UL1363 (Power Tap)                  | UL1363                    |
| Canada                              | cUL                       |
| WARRANTY                            |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>