

## 7-Outlet Home/Business Theater Surge Protector, 6-ft. Cord, 2100 Joules, Tel/Modem/Coax Protection

MODEL NUMBER: HT706TSAT



### Highlights

- 7 outlets / 6 ft. cord
- 2100 joule rating
- 2-line 2.2 GHz gold coaxial surge protection
- 1-line tel/modem surge protection

### Package Includes

- HT706TSAT Home/Business Theater Surge Suppressor
- 6 ft. gold coaxial cable
- 6 ft. phone cord
- Instruction manual with warranty information

### Description

Tripp Lite's HT706TSAT Home/Business Theater Surge Suppressor provides high-performance protection--2100 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 7 outlets (with transformer spacing), 2-line 2.2 GHz coaxial protection and 1-line tel/modem protection safeguard an entire home/business theater system. \$100,000 Ultimate Lifetime Insurance coverage (U.S., Canada, and Puerto Rico only). Includes two diagnostic LEDs, 6 ft. cord with a right-angle plug, 6 ft. coaxial cable and 6 ft. phone cord.

### Features

- 2100 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$100,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected components against surge damage...for life!
- 7 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely-spaced outlets accommodate up to 4 transformers
- 2 sets of surge-protected 2.2 GHz gold coaxial connectors (with included 6 ft. gold coaxial cable)
- 1 set of surge-protected tel/modem connectors (with included 6 ft. phone cord) safeguard personal video recorders (PVRs) on a single dial-up line
- 6 ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 2 diagnostic LEDs alert user to protection and grounding status



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

- Keyhole slots provide convenient wall or cabinet mounting
- Illuminated master switch provides one-touch power control over all components. Integrated circuit breaker protects against dangerous system overload
- High-impact plastic housing (black) stands up to the most demanding environments
- UL and CSA listed
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

## Specifications

| OVERVIEW                           |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| UPC Code                           | 037332121486                                                                      |
| OUTPUT                             |                                                                                   |
| Frequency Compatibility            | 50 / 60 Hz                                                                        |
| Output (Watts)                     | 1800                                                                              |
| Output Receptacles                 | (7) 5-15R                                                                         |
| Circuit Breaker (amps)             | 15                                                                                |
| Transformer Accommodation          | (4) Yes                                                                           |
| Right-Angle Outlets                | Yes                                                                               |
| INPUT                              |                                                                                   |
| Nominal Input Voltage(s) Supported | 120V AC                                                                           |
| Recommended Electrical Service     | 120V (110-125V)                                                                   |
| Input Cord Gauge Type              | 14 gauge; SJT                                                                     |
| Voltage Compatibility (VAC)        | 120                                                                               |
| Maximum Surge Amps                 | 75000                                                                             |
| Input Plug Type                    | NEMA 5-15P                                                                        |
| Input Cord Length (ft.)            | 6                                                                                 |
| Right-Angle Plug                   | Yes                                                                               |
| Input Cord Length (m)              | 1.83                                                                              |
| Integrated Cord Clip               | No                                                                                |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                   |
| Diagnostic LED(s)                  | Yes                                                                               |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                                      |                                                                                                                |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Diagnostic LED Details                               | Built-in LEDs confirm protection and grounding status                                                          |
| <b>SURGE / NOISE SUPPRESSION</b>                     |                                                                                                                |
| AC Suppression Joule Rating                          | 2100                                                                                                           |
| AC Suppression Response Time                         | < 1 ns                                                                                                         |
| Protection Modes                                     | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                             |
| Clamping Voltage (RMS)                               | 150                                                                                                            |
| UL1449 Let Through Rating                            | 400, 400, 500                                                                                                  |
| EMI / RFI Filtering                                  | Up to 40 dB                                                                                                    |
| Automatic Shut-Off                                   | Yes                                                                                                            |
| <b>DATALINE SURGE SUPPRESSION</b>                    |                                                                                                                |
| Telephone/DSL Protection                             | Yes                                                                                                            |
| Telephone/DSL Protection Details                     | 1 line                                                                                                         |
| Cable (Coax) Protection                              | Yes                                                                                                            |
| Cable (Coax) Protection Details                      | 2 line                                                                                                         |
| Network (Ethernet) Protection                        | No                                                                                                             |
| <b>PHYSICAL</b>                                      |                                                                                                                |
| Anti-Microbial Protected                             | No                                                                                                             |
| Color                                                | Black                                                                                                          |
| Color (AC Line Cord)                                 | Black                                                                                                          |
| Integrated Keyhole Mounting Slots                    | Yes                                                                                                            |
| Keyhole Slot Mounting Measurement (Center to Center) | 160mm                                                                                                          |
| Material of Construction                             | Plastic                                                                                                        |
| Outlets Measurement (Center to Center)               | Distance between transformer outlet and standard outlet = 38.10mm; Distance between standard outlets = 25.40mm |
| Receptacle Color                                     | Black                                                                                                          |
| Shipping Dimensions (hwd / cm)                       | 64.01 x 36.07 x 15.24                                                                                          |
| Shipping Dimensions (hwd / in.)                      | 25.20 x 14.20 x 6.00                                                                                           |
| Shipping Weight (kg)                                 | 0.82                                                                                                           |
| Shipping Weight (lbs.)                               | 1.80                                                                                                           |
| Unit Dimensions (hwd / cm)                           | 3.81 x 35.56 x 8.26                                                                                            |
| Unit Dimensions (hwd / in.)                          | 1.5 x 14 x 3.25                                                                                                |
| Unit Weight (kg)                                     | 0.54                                                                                                           |
| Unit Weight (lbs.)                                   | 1.2                                                                                                            |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

| SPECIAL FEATURES                                           |                                                                                                                                   |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Rotatable Outlets                                          | No                                                                                                                                |
| CERTIFICATIONS                                             |                                                                                                                                   |
| UL1449 3rd Edition (AC Suppression)                        | UL1449 3rd Edition                                                                                                                |
| UL1363 (Power Tap)                                         | UL1363                                                                                                                            |
| UL497A (Communications)                                    | UL497A                                                                                                                            |
| FCC Part 68 (Communications)                               | FCC Part 68                                                                                                                       |
| Canada                                                     | CSA                                                                                                                               |
| Approvals                                                  | Exceeds IEEE 587 category A&B specifications                                                                                      |
| WARRANTY                                                   |                                                                                                                                   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                                         |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$100,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>