


Item no.: 769-645/004-000
Product description: Plug MATING DIRECTION PERPENDICULAR TO PCB 1 X 1
MM / 0.039 X 0.039 IN PIN SPACING 5 MM / 0.197 IN 15 POLE



Produkt kann von Bild abweichen / product may differ

Packing unit 15 pieces

RoHS compliant

Measured shock voltage	4 kV
Strip length from	8 mm
Measured voltage EN	500 V
Pollution degree	2
Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	15
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Weight	15.815 g
Color	gray
Wiring type	Front-entry
No. of connection Points	15
No. of potentials	15
Height	22.2 mm
Height	0.874 in

Width	89.7 mm
Width	3.531 in
Depth	18.3 mm



Depth	0.72 in
Customs Tariff No.	85369010
Country of Origin	Deutschland



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
769-645/004-000	ABS	05-HG476175/3-PDA	500	32	4
769-645/004-000	CSA	154112-1101144	300	20	28-12
769-645/004-000	KEMA	2077750.01	500	32	4
769-645/004-000	UR	E45171	600	20	16-12
769-645/004-000	UR	E45172	300	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected