

**SAK terminal with screw connection
SAKG 40 II**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The Weidmüller SAKG range includes the following connection types:

- Combined clamping yoke/flat-blade connection, version I
- Flat spade connection, version II.

Here, two types of cable glands are intended:

- a) screw set with lock nut
- b) with threads on the busbar clamping yoke connection, version III.

The stripped conductor can be connected without any further preparation.

General ordering data

Order No.	0170520000
Type	SAKG 40 II
Version	SAK terminal with screw connection, Special terminal, Rated cross-section: 95 mm ² , Screw connection, KrG, Medium yellow
GTIN (EAN)	4008190049911
Qty.	10 pc(s).

SAK terminal with screw connection SAKG 40 II

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions

Length	90 mm	Width	46 mm
Height	53 mm	Height of lowest version	53 mm
Weight	242.4 g	Net weight	236 g

Temperatures

Operating temperature		Storage temperature	
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C

Additional technical data

Explosion-tested version	No	Number of similar terminals	1
Open sides	Open	Type of mounting	Snap-on
Version	Stud terminal		

CSA ratings data

Certificate No. (CSA)	12400-119	Voltage size C (CSA)	600 V
Current size C (CSA)	250 A	Wire cross section max. (CSA)	0000 AWG
Wire cross section min. (CSA)	00 AWG		

Clampable wires (rated connection)

Type of connection	Screw connection	Connection direction	on side
Number of connections	1	Clamping range, rated connection, min.	10 mm ²
Clamping range, rated connection, max.	95 mm ²	Clamping screw	M 10
Tightening torque, min.	10 Nm	Tightening torque, max.	20 Nm
Wire connection cross section, solid core max. rated connection	16 mm ²	Wire connection cross section AWG, min.	AWG 20
Wire connection cross section AWG, max.	AWG 4/0		

Rated data

Rated cross-section	95 mm ²	Rated voltage	1,000 V
Rated impulse withstand voltage	8 kV	Rated current	232 A
Current at maximum wires	232 A	Standards	IEC 60947-7-1
Pollution severity	3		

UL ratings data

Certificate No. (UR)	E60693VOL1SEC2	Voltage size C (UR)	600 V
Current size C (UR)	230 A	Conductor size Factory wiring max. (UR)	0000 AWG
Conductor size Factory wiring min. (UR)	1 AWG	Conductor size Field wiring max. (UR)	0000 AWG

Material data

Insulating material	KrG	Material	KrG
Colour	Beige	UL 94 flammability rating	V-0

SAK terminal with screw connection SAKG 40 II

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

System specifications

Product family	SAK terminal with screw connection	Type of connection	Screw connection
Connection direction	on side	Number of levels	1
Number of connections	1	No. of clamping points per level	2
Levels cross-connected internally	No	Mounting rail	TS 32
End cover plate required	Yes		

Classifications

ETIM 2.0	EC000897	ETIM 3.0	EC000897
UNSPSC	30-21-18-11	eClass 4.1	27-14-11-31
eClass 5.1	27-14-11-31	eClass 6.0	27-14-11-20
eClass 7.0	27-14-11-20		

Product information

Descriptive text technical data	Conductor connection with cable lugs according to DIN 46234, from 10 .. 95 mm ²
---------------------------------	--

Approvals

Approvals

