

**Industrial Ethernet
IE-MCT-1RS232/485-1ST****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Product image**Serial/fibre-optic converter**

Media converter for implementing serial, copper-based interfaces on fibre-optic cables and vice versa. Facilitates communication between terminal devices with type RS232/422/485 serial interface over a distance of up to 5 km.

- Ring and point-to-point transmission modes
- Extension of the RS232/422/485 transmission to up to 5 km
- Supports baud rates of 50 bps to 921.6 Kbps
- Expanded temperature range of -40 to 75°C
- Compact design

General ordering data

Type	IE-MCT-1RS232/485-1ST
Order No.	1362950000
Version	Serial/fibre-optic converter, 1 x terminal block for RS232/422/485, 1 x ST multimode, IP30, -40 °C...75 °C
GTIN (EAN)	4050118165203
Qty.	1 pc(s).

Industrial Ethernet IE-MCT-1RS232/485-1ST

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Width	90.2	Width (inches)	3.551 inch
Height	100 mm	Height (inches)	3.937 inch
Depth	22 mm	Depth (inches)	0.866 inch
Net weight	130 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Serial interface

Baud rate	50 bit/s to 921.6 kbit/s	Interface standards	RS-232/422/485
RS485 data direction control	ADDC® (automatic data direction control)		

fibre-optic interface

Receive sensitivity	-20 dBm	Transmission mode: "Point-to-point"	Half-duplex, Full-duplex
Transmission mode: "Ring"	Half-duplex	Transmit power	> -5 dBm
Type of connection		Typical distances	5 km (50/125, 62.5/125, 100/140 µm multimode cable)
	ST connection, Multimode		
Wave length	850 nm		

EMC conformity and approvals

EMC standards	FCC Part 15 Class B, EN 61000-4-2 (ESD), Stage 3, EN 61000-4-3 (RS), Stage 2, EN 61000-4-4 (EFT), Stage 2, EN 61000-4-5 (Surge), Stage 3, EN 61000-4-6 (CS), EN 61000-4-8, Stage 1, cULus	Safety standard	UL 60950-1
---------------	---	-----------------	------------

Environmental conditions

Humidity	5 to 95 % (non-condensing)	Operating temperature, max.	75 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	75 °C
Storage temperature, min.	-40 °C		

Guarantee

Time interval	5 years
---------------	---------

MTBF

MTBF	780,480 hrs	Database	Telcordia (Bellcore), GB
------	-------------	----------	--------------------------

Power supply

Connection type	1 removable 3-pole terminal block
-----------------	-----------------------------------

Industrial Ethernet
IE-MCT-1RS232/485-1ST**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Current consumption	Voltage	12 V DC
	Current	140 mA
	Voltage	24 V DC
	Current	67.7 mA
	Voltage	48 V DC
	Current	28.7 mA
Overload current protection	1.1 A	
Reverse polarity protection	Available	
Supply line protection	2 KV Burst (EFT), EN61000-4-4, 2 KV Surge, EN61000-4-5	
Voltage supply	24 V DC, 1 single input	
Voltage supply range	Voltage type	DC
	Voltage, min.	12 V
	Voltage, max.	48 V

Serial signals

RS232	Tx, Rx, GND	RS422	TxD+, TxD-, RxD+, RxD-, GND
RS485 2-wire	Data+, Data-, GND	RS485 4-wire	TxD+, TxD-, RxD+, RxD-, GND

Technical data

Housing main material	Aluminum	Protection degree	IP30
Type of mounting	Mounting plate, Wall mounting, when screwed in, TS 35, (with optional mounting kit IE-DINRAILMOUNT-KIT 1504430000)		

Classifications

ETIM 6.0	EC000310	ETIM 7.0	EC000310
eClass 9.0	19-17-01-14	eClass 9.1	19-17-01-14
eClass 10.0	19-17-04-11		

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity
Brochure/Catalogue	CAT 9 IETH 18/19 EN
Engineering Data	STEP
User Documentation	Hardware Installation Guide