

**Crimping contact
HDC-C-M5-BM4.0AG****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16


D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Crimps provide a electrical and mechanical connection between wire and contact that is both secure and reliable. The optimal crimp connection is gas-tight and corrosion-resistant.

General ordering data

Type	HDC-C-M5-BM4.0AG
Order No.	1682410000
Version	Heavy Duty Connectors, Contact, CM 5, Female, Conductor cross-section, max.: 4, turned, Copper alloy
GTIN (EAN)	4008190474140
Qty.	100 pc(s).

**Crimping contact
HDC-C-M5-BM4.0AG**
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data
Dimensions and weights

Net weight	1.51 g	Diameter	4.1 mm
------------	--------	----------	--------

General data

Contact diameter, male Ø	2.5 mm	Production methods	turned
Stripping length, rated connection	7.5 mm	Type	Female
Type of connection	Crimp connection	Material	Copper alloy
Surface finish	silver	Volume resistance	≤ 2mΩ

Classifications

ETIM 3.0	EC000796	UNSPSC	30-21-18-01
eClass 5.1	27-14-34-19	eClass 6.2	27-26-12-02
eClass 7.1	27-44-02-04		

Product information

Descriptive text accessories	For further accessories, see chapter J - tools, see chapter K
------------------------------	---

Approvals

Approvals



ROHS	Conform
------	---------

Crimping contact HDC-C-M5-BM4.0AG

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold


Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Drawings



Leiterquerschnitt	Abisolierlänge	
0,75 - 1,00 mm ²	AWG 18	8 mm
1,50 mm ²	AWG 16	8 mm
2,50 mm ²	AWG 14	8 mm
4,00 mm ²	AWG 12	8 mm

