

SAI cable
SAIL-M8G-4-10Q**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-2083

www.weidmueller.com



Different machine designs often call for custom cable lengths. Sensor cables supplied with a connector at one end only are easy to adapt to the respective circumstances. The cables are available in different versions:

straight, angled and with all standard pole counts (3, 4, 5, 7, 8 and 12 poles). Customisable plugs and sockets are used for building individual connecting cables. The cable sheath is made from PVC/PVC, PUR/PVC or PUR, is free from halogens and suitable for moving cable carriers. Plugs and cables are supplied in neutral black.

General ordering data

Order No.	1926991000
Type	SAIL-M8G-4-10Q
Version	Round plug-in connector, Cable, One end without connector, LED: No, 10 m, PUR/ TPE
GTIN (EAN)	4032248573912
Qty.	1 pc(s).

S&I cable
SAIL-M8G-4-10Q

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com

Technical data
Dimensions

Net weight 266 g

General data

Bending radius, min., moving	10 x cable diameter	Bending radius, min., stationary	10 x cable diameter
Cable diameter, max.	4.6 mm	Cable diameter, min.	4.2 mm
Cable length	10 m	Conductor O.D.	-
Contact material, pin	CuZn35PB2	Contact material, socket	CuZn35PB2
Contact surface	Gold-plated	Contact tube diameter	M8
Core cross-section	0.25 mm ²	Housing main material	PUR
Material	PUR/ TPE	No. of poles	4
Pollution severity	3	Protection degree	IP 67
Rated current	4 A	Rated voltage	30 V
Sheathing colour	black	Temperature range of housing	-25...+85 °C
Type of connection	Pin	jumpered	No

Classifications

ETIM 2.0	EC000304	ETIM 3.0	EC001855
UNSPSC	26-12-16-13	eClass 4.1	27-06-00-00
eClass 5.1	27-06-91-90	eClass 6.0	27-06-91-90
eClass 7.0	27-06-91-90		