

CBX100USB**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



The CBX 100/CBX 200 USB interfaces for PC-based configuring and calibrating of the ITXPlus universal signal isolating converters, WAVE TTA and the ACT20 series.

The CBX 100/200 USB interface converters have a status LED to display the transmit/receive mode. The driver software is available for on our web site.

General ordering data

Type	CBX100USB
Order No.	7940025031
GTIN (EAN)	4032248751136
Qty.	1 pc(s).

CBX100USB**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	213 g
------------	-------

Temperatures

Humidity	10...90 % (no condensation)	Operating temperature	-20 °C...+70 °C
Storage temperature	-25 °C...+70 °C		

Output

Status indicator	LED (send / receive)
------------------	----------------------

General data

Input/Output	Interfaces
--------------	------------

Insulation coordination

Insulation voltage	500 V for 60 s	Standards	DIN EN 50178, DIN EN 61000-4-2
--------------------	----------------	-----------	--------------------------------

Classifications

ETIM 3.0	EC002304	UNSPSC	30-21-18-01
eClass 6.2	27-06-92-02		

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Declaration of Conformity	Declaration of Conformity.pdf
---------------------------	---